

Leather Specialties

PROFILE

Leather Chemicals Division is one of the few vendors in the world that produces all kinds of chemicals needed for leather products. We supply inorganic/synthetic preservatives, dyes, pigments, softeners, tanning and finishing supplements etc.

| Product | Product Name | Application medium *) W = waterborne, S = solventborne | Product description |
|-------------------------|--------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Beam house | Peltec AN2C | W | Non-ionic degreasing agent, resistant to electrolytes and hard water, outstanding emulsifying and dispersing power for fats, fatty acids, metallic soaps, waxes and dirt of all kinds. It can be used in both the alkaline and acid pH range. |
| | Preventol Z-L | W | Sodiumdimethyldithiocarbamate, contents: 40-42%, pH=9-10 Preventol Z-L is stable to pH 7-13 |
| | Preventol WB Plus L | W | p-cloro-m-cresol, 2 phenolphenyl and pyrrithione, pH 10.5 It has broad spectrum of activity against mold fungi that can damage leather. Suitable for preserving wet blue, wet white, vege tanned leather |
| | Peltec SE | W | bacterial enzyme, hydrolysis unstructured proteins, degradation of albumin and globulin, speeding up the soaking, very good rewetting in soaking, excellent biodegradability |
| Liming auxiliary | Peltec UAL | W | It is an environmental friendly liming auxiliary based on special organic alkali products. It offers advantages of good opening ups, relieves of wrinkles, reductions to growth marks without loosening the pelt substances to produce leather with better fullness. It effectively controls the pelt substances in the belly and flank areas to ensure good evenness of the whole hide/skin and to avoid looseness. pH=10-12.00 |
| | Blancorol BA-IN | W | pH regulator, increases the pH in the soaking slowly and equally, no danger of pH peaks and alkaline swelling, adjusts the pH to 9,2-9,8, the optimum pH range for soaking and soaking enzymes |
| | Peltec BG | W | bacterial enzyme, optimum grain elasticity without the tendency of loose grain, compact leathers with a good inner softness, a round handle and a tight fine grain |
| Tanning | Cromosal B | W | Basic chromium sulfate, Cr2O3 content: 26%, Basicity approx 33 %, Suitable for all type of tanning |
| | Blacorol ZB-33 | W | Zirconium sulfate, ZrO2 content: 33% |
| Colourant | Levaderms | W/S | Anionic dyestuffs in aqueous-organic solution which can be used for through-feed dyeing and in the finishing for spray dyeing, special effect in top coats |
| Retanning/ Fatliquoring | Tanigan PAK | W | Lightfast, anionic retanning material in powder form with a pronounced neutralizing and buffering effect and good dyeing properties. pH=6.8 |
| | Tanigan ISG, Tanigan PR, Baykanol SL | W | pH=6.5. It is for levelling of dyestuff and dispersing for vegetable tanning material |
| | Retingan R7 | W | pH=9.3, Anionic resin tanning material with low astringency and selective filling effect for retannage of all types of leather |
| | Tanigan AN | W | pH=3.2, Replacement syrtan for tannage and retannage of firmer leather with tight grain |
| | Tanigan BN | W | pH=3.2, Replacement syrtan for tannage and retannage for soft, full, almost white leather with mellow grain |
| | Tanigan 3LN, Tanigan HO | W | pH=3.0 Non bleaching syrtan for white leather where high lightfast and heat yellowing properties are required as well as for colored leather because of excellent dyeing and dry-drumming properties |
| | Tanigan OS | W | pH=3.6, Anionic, synthetic, general purpose replacement tanning material |
| | Tanigan CLS-50 | W | pH=1.9, Special syrtan for the manufacturing of shrunken grain leather |
| | Tanigan F | W | pH=3.2, Syrtan for tannage and retannage of leather with high temper and good fullness. Also it can replace to Chestnut |
| | Tanigan VR | W | pH=3.2, Anionic, lightfast syrtan for the tannage and retannage, suitable as replacement for vegetable tanning materials, also it can replace to Mimosa |
| | Levotan GTA-C | W | pH=2.0, Waterborne solution of glutaraldehyde which can be used in various steps of the leather manufacturing process |
| | Levotan LB | W | pH=6.0, Softening and filling polymer tanning material based on modified polyamide carboxylic acid for the retannage of wet blues and vegetable leather. |
| | Bahcorol CGA-C | W | Anionic, Special auxiliary for wet blue hides and skins. Sulfate free deliming agent. Suitable for application in the retannage of splits. |
| | Leukotan 1093 | W | pH=8.0, concentration: 40% High solid acrylic retanning material for soft leather with tight grain and excellent fullness |
| | Leukotan 8090 | W | pH=7.0, concentration: 46%, Acrylic polymer syrtan with a balanced composition of molecular weight to fill the more open and loose areas of leather, it supports a tight flat grain and it's not plumping |
| Leukotan 970 | W | pH=4.4, concentration: 32%, Acrylic replacement syrtan with an excellent softening and filling effect, disperses vegetable extracts very well and promote uniform dyeing It has tanning capabilities | |
| | Primal SB-100 | W | pH=7.5, Solid contents: 35%, Very soft acryl binder with high wet and dry flex, cold crack resistant, good print retention, fill and coverage and plate release |
| | Primal SB-150 | W | pH=7.5, Solid contents: 35%, Soft acryl binder with high coverage, good print retention and plate release for base coat |

| | | | | |
|-----------------|-----------------------------|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Finishing agent | Primal 191 | W/S | pH=8.9, solid contents: 23%, Acryl copolymer based feel agent to obtain a pleasant, waxy surface touch, like as grip feel(specially for base ball glove and base ball) | |
| | Primal 863 | W | pH=5.2, Solid contents:35%, Soft acrylic emulsion for impregnation and base coat. Soft, tough, tack-free | |
| | Primal FGR | W | pH=8.0, Solid contents: 23%, Acrylic polymer for impregnation and base coat with very good penetration power. | |
| | Aquaderm Finish LB | W | pH=7-8, Solid contents:37%, characterised in particular by good wet and dry rub fastness and cold flex resistance.improves the embossing properties and reduces tackiness on hot-plating and stacking to a minimum | |
| | Bayderm Bottom 10UD | W | pH=7.0, Solid contents:30%, Soft, non-tacky aliphatic P.U dispersion/ It can be used as non-ionic P.U dispersion | |
| | Bayderm X-Tra Finish TV | W | pH=8.5 Solid contents: 20%, Medium Hard high gloss aliphatic P.U binder for base and top coat | |
| | Bayderm Bottom 50UD | W | pH=9.0 Solid contents: 40%, Medium hard aliphatic/aromatic P.U binder for base and Top coat | |
| | Baysin Lustre 2062 | W | pH=7.5-9.0, Highly transparent protein based binder ,high glossy | |
| | Baysin X-Tra Luster P21 | W | pH=8.5 Solid contents: 12%, Polyamid protein binder, good for rub fastness | |
| | Euderm Luster L | W | pH=8.0 Solid contents:8%, Casein with wax | |
| | Euderm Compact UP-E | W | pH=8.5, Solid contents:21%, Compact binder for base coat with very good for print retention | |
| | Euderm Nappa soft S2 | W | pH=9.6, Solid contents:26%, Anti tack and matting agent with filling effect | |
| | Euderm Paster KPS-C | W | Cationic stucco | |
| | Euderm X-grade CGS2 | W | pH=9.0 Solid contents:32%.Acryl based stucco for corrected grain | |
| | Euderm X-Tra Oil L | W | Solid contents: 100%, Natural Oil to get slightly bunished effect and soft touch | |
| | Baygen Compact Bottom APS 2 | W | pH=8.0, Solid contents: 28%, P,U and Acryl mixed compact binder for patent leather | |
| | Baygen Compct DD | W | pH=8.0, Solid contents: 26%, P,U and Acryl mixed compact binder for patent leather | |
| | Baygen Hardener SN02 | S | Solid content: 58%, Polyisocyanate crosslinker for patent leather | |
| | Baygen Hardner LRF | S | Solid contents: 60%, Polyisocyanate crosslinker for patent leather with good light fastness | |
| | Baygen Top U 01 | S | Solid contents: 71%, Polyester based lacquer with excellent properties | |
| | Baygen Top TF | S | Solid contents: 57%, Polyester based lacquer with excellent properties to thermosetting | |
| | Baygen Deep Black R | S | Solid contents: 57%, Polyester based lacquer with excellent properties | |
| | Baygen Top White B | S | Solid contents: 57%, Polyester based lacquer with excellent properties to light fastness | |
| | Aquaderm XL-50 | W/S | Solid contents: 50%, Reactive aliphatic polyisocyanate cross- linker to improve overall fastness | |
| | Binder LS 3492 | W/S | Solid contents:49-51%, reactive aliphatic polyisocyanate resin based cross-linker to improve overall fastness such as toughness, abrasion resistance, and cold crack resistance by crosslinking the coating film. | |
| | Acrysol RM 825 | W | pH=7.0, Solid contents:25%, Polyurethane based thickner | |
| | Acrysol RM 1020 | W | pH=7.0, Solid contents:20%, Polyurethane based thickner | |
| | Aquaderm X-Shield G | W | pH=7.0, Solid contents: 40%, Fluorine containing copolymer for anti-soiling leather | |
| | Aquaderm X-Shield L | W | pH=5.5, Solid contents: 25%, Fluoroacrylate copolymer and adductive for anti-soiling leather | |
| | Rosilk 2229W | W | pH=8.0, Solid contents: 45%, Silicone polymer emulsion for unique dry feel, excellent gasoline rubs,excellent taber value, white line and white break resistance. | |
| | Colourant | Chromtec GC | Cromtec GC: Chemical Grain size:100 µm Cr2O3: 10% SiO2:2% Fe2O3:45% | * The colourant is mixed with the clays before burning * Colourants are based onmetals and their oxides and mixtures of them * Cromtec GC can be used for „Grey“ coloured bricks |

Supplier

LANXESS
Energizing Chemistry